

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** *Universal Oilspray REF 177939, 177940*
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Lubricant*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** *ORBIS Dental Handelsgesellschaft mbH
Schuckertstr. 21, D-48153 Münster
+49 (0) 251 / 3226786
+49 (0) 251 / 7607201
E-Mail: info@orbis-dental.de*
- **Further information obtainable from:**
Information Center of poisoning and hazards University of Bonn
- **Emergency telephone number:** *Tel.: +49(0) 228 19240 / Telefax: +49(0) 228 28733314*

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



F+; Extremely flammable

R12: Extremely flammable.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02

- **Signal word** *Danger*

- **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

(Contd. on page 2)

Trade name: Universal Oilspray





(Contd. of page 1)

- **Additional information:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
Keep out of the reach of children
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 74-98-6 EINECS: 200-827-9	propane	 F+ R12  Flam. Gas 1, H220; Press. Gas, H280	25-50%
CAS: 106-97-8 EINECS: 203-448-7	butane	 F+ R12  Flam. Gas 1, H220; Press. Gas, H280	10-25%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:**
 Ensure adequate ventilation.
 Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
 See Section 7 for information on safe handling.

(Contd. on page 3)

Trade name: Universal Oilspray

(Contd. of page 2)

See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
 Do not spray onto a naked flame or any incandescent material.
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 Store in a cool location.
 Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep container tightly sealed.
 Do not seal receptacle gas tight.
 Store in cool, dry conditions in well sealed receptacles.
 Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**
 The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Trade name: Universal Oilspray

(Contd. of page 3)

- **As protection from splashes gloves made of the following materials are suitable:**
 Butyl rubber, BR
 Nitrile rubber, NBR
 Natural rubber, NR
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol
 Compressed liquefied gas

Colour: Clear

· **Odour:** Characteristic

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44 °C

· **Flash point:** -97 °C

· **Ignition temperature:** 365 °C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.5 Vol %

Upper: 10.9 Vol %

· **Vapour pressure at 20 °C:** 4.5 bar

· **Density at 20 °C:** 0.66 g/cm³

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Solvent content:

Organic solvents: <60 %

VOC (EC) 59

Solids content: 0

· **Other information** No further relevant information available.

10 Stability and reactivity

· Reactivity

· Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** No further relevant information available.

(Contd. on page 5)

Trade name: Universal Oilspray

(Contd. of page 4)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Generally not hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04	gases in pressure containers (including halons) containing dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

(Contd. on page 6)

Trade name: Universal Oilspray

(Contd. of page 5)

· **Transport hazard class(es)**· **ADR**

· **Class** 2 5F Gases.
 · **Label** 2.1

· **IMDG, IATA**

· **Class** 2.1
 · **Label** 2.1

· **Packing group**· **ADR, IMDG, IATA** Void· **Environmental hazards:**· **Marine pollutant:** No· **Special precautions for user** Warning: Gases.· **Danger code (Kemler):** -· **EMS Number:** F-D,S-U

· **Transport in bulk according to Annex II of
 MARPOL 73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**· **ADR**· **Excepted quantities (EQ):** E0· **Limited quantities (LQ)** 1L· **Transport category** 2· **Tunnel restriction code** D· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**

GHS02

· **Signal word** Danger· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 7)

Trade name: Universal Oilspray

(Contd. of page 6)

- P251 Do not pierce or burn, even after use.
 P211 Do not spray on an open flame or other ignition source.
 P271 Use only outdoors or in a well-ventilated area.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 · **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
 H280 Contains gas under pressure; may explode if heated.
 R12 Extremely flammable.

· Department issuing MSDS: Abteilung Produktsicherheit

· Contact: Hr. Dr. Metz

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)

· * Data compared to the previous version altered.